

DECT RFPI SNIFFER PRO

Industrial PDA with integrated DECT module

for detection and measuring of DECT base stations

CHARACTERISTICS

- Simple, intuitive operation, similar to a spreadsheet
- Storage of the measurement processes in tables with locations and assigned readings
- Import of building construction plans for storage of the measured spots and base stations
- Measurement of the RSSI value (% and dBm) and the connection quality (%)
- Measurement results are displayed as a list (Min/Max/Average)
- Measurements possible of any base stations without registration (measure on dummy bearer)
- RFPI Scan of all base stations located in the HF range (RFPI and RPN display)
- Identification of known stations, of which RFPI or EMC are stored in a table
- Internal or external antenna (TNC connector)
- Operation time min. 8 hours without battery recharge
- Easily exchangeable battery, data maintained over backup battery during exchange
- External battery charger for spare rechargeable battery
- Connects to PC via USB or Bluetooth for Data transfer and printing of the measurement protocol
- Handy, robust industrial PDA (IP65)
- Holster for mobile use, e.g. ladder climbing
- Safe storage in the included case



DELIVERY INCLUDES

- Case for safe storage and transport
- Psion PDA with integrated DECT sniffer
- PDA Charging Station (cradle with USB cable for connection to a PC)
- External DECT antenna (TNC connector)
- Additional charger for spare rechargeable battery
- Spare rechargeable battery
- 2 power plugs for the charging stations
- Holster for PDA
- Installation CD and Quick Start Guide