

CRADLE FOR HONEYWELL CT40 / CT40 XP

TISPLUS Vehicle Cradle for Honeywell CT40 / CT40 XP

The TISPLUS vehicle cradle for Honeywell CT40 / CT40 XP allows easy insertion of the device with secure locking mechanism, one-hand operation and reliable charging function.

ITEM NUMBERS

24-40-09-TPC



AT A GLANCE

- Functional, compact and robust design
- Easy insertion and removal of the device
- Safe locking and one-hand operation
- Spring-mounted contacts (pogo pins) for safe charging
- Screw holes on the front panel allows easy installation on the dashboard
- Compatible with RAM Mount, by a variety of mounting options
- Cable with USB-A plug for USB charging adapter

TECHNICAL SPECIFICATIONS

DIMENSIONS AND WEIGHT

- 183x84x36mm
- 130g (without Device and RAM mount)

INPUT VOLTAGE

1,4m cable with USB-A plug for USB charging adapter
Delivery incl. USB vehicle charging adapter Input 12/24V 9-30V,
Output 5V 2x 2.4A

TEMPERATURE RANGE

- Operating temperature: -20 °C to + 70 °C
- Storage temperature: -40 °C to + 85 °C

Mobile device and RAM mount not included in delivery.