



On the following pages you will find detailed manufacturer information about this product from our TISWARE hardware and software portfolio.

If you need more information, please contact us!

If you have any questions about or are interested in this or other products from our portfolio, please contact our sales team. Our colleagues are happy to help.

Phone: +49 2871 2722-0 E-mail: contact@tis-gmbh.com

Other products from the TIS GmbH portfolio



TISLOG TELEMATICS SOFTWARE

TISLOG logistics and transport software provides powerful and flexible solutions for mobile order management, capable of exactly what you need for the individual work processes of your business.



www.tislog.com



TISPLUS HARDWARE ACCESSORIES

TISPLUS - Clever accessories for ergonomic handling on the go and in the warehouse. und im Lager. Development, design and production of our TISPLUS products take place at 100% in Germany.



www.tisplus.com

BACKGROUND TIS GMBH

The TIS GmbH, based in Bocholt is one of the market leaders for sophisticated telematics projects. TIS stands for "Technical Information Systems". Since 1985 the company develops intelligent telematics solutions for freight forwarders, transport and logistics companies and retail chains. Currently, more than 50 employees work for TIS. The latest generation of products are the platform-independent software solutions under the brand name TISLOG Logistics & Mobility. Together with the powerful hardware of renowned partners and the in-house developed hardware accessories TISLOG builds the optimal solution for companies looking for professional telematics solutions.

More information on the TIS Gmbh and our portfolio of software, hardware and accessories on

www.tis-gmbh.com

POWERSCAN™ PM8300

ODATALOGIC





TECHNOLOGY DRIVEN

The PowerScan PM8300 series includes different models able to satisfy all customers' needs; the PM8300 is the basic cordless model; the PM8300-D intermediate model includes a display and 3-key keypad; and the ultimate PM8300-DK model features a display and a full 16-key keyboard. The PM8300-DK model significantly increases the sophistication of interaction with the host system and opens up new potential uses of the scanner, making it suitable for applications that would normally require a more expensive portable data terminal. The BC9180 used in compatibility mode, also includes in one model two different Ethernet connections: Standard Ethernet and Industrial Ethernet protocols such as Ethernet IP and Modbus.

DATALOGIC'S STAR CORDLESS SYSTEM™

Narrow band radio communications with Datalogic's STAR Cordless System™ provides the key to increased productivity and flexibility in the workplace. It offers scalable solutions from simple point-to-point applications to networking capabilities combined with seamless roaming for complex installations.

GOOD-READ FEEDBACK AND SUPERIOR READING PERFORMANCE

The PM8300 readers feature Datalogic's exclusive 3 Green Lights (3GL™) for superior good-read feedback. The patented 'Green Spot' directly on the code and dual Good Read LEDs on the top and back of the cap adds increased visibility at any angle. Superior reading performance is enhanced by Datalogic's patented PuzzleSolver™ technology for fast and accurate reading of standard, poorly printed and damaged codes.













FEATURES

- Optics available in Standard Range (contact up to 1.0 m / 3.3 ft) and Auto Range (20 cm / 8 in up to 12.5 m / 41.0 ft)
- Available in 3 models: basic, with display and 3-Key keypad, with display and full alphanumeric keypad
- 100% Compatible with Datalogic's STAR Cordless System™
- Radio frequencies available in 433 MHz or 910 MHz
- Point-to-point and multi-point transmission
- Seamless roaming
- Ethernet Connectivity (Standard and Industrial)
- Datalogic 3GL™ and loud beeper for good read feedback
- User replaceable lithium-ion battery
- Operates over a wide range of temperatures
- Water and Particulate Sealing Rating: IP65 / IP64 (with display)
- Drop resistance to 2.0 m / 6.5 ft
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY-APPLICATIONS

- Manufacturing / Warehouse
- Retail / POS Check-out
- Transportation & Logistics / Warehouse / Sorting

POWERSCAN™ PM8300

ODATALOGIC

630 - 680 nm VLD

35 +/- 5 scans/sec.

Skew (Yaw): +/- 60°

PM83X0: 0.076 mm / 3 mils;

Click' Trigger

CORDLESS COMMUNICATIONS

Max. Readers in Same Area: 2000 Max. Readers per Radio Receiver: 32 Radio Frequency: 433.92 MHz; 910 MHz Radio Range (Open Air): 433.92 MHz: Up to 50 m / 164 ft

910 MHz: Up to 30 m / 98 ft

Seamless Roaming; Two Way Communications

DECODING CAPABILITY

1D / LINEAR CODES Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.

STACKED CODES Code 16K; Code 49; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar

Stacked Omnidirectional

ELECTRICAL

BATTERY Battery Type: Li-lon 2150 mAh;

Charge Time: External Power: 4 Hours; Host Power: 10 Hours:

Reads per Charge: +60,000

CRADLE INDICATOR LEDS Battery Charging (Red); Charge Completed (Green);

Power/Data (Yellow) Operating (Typical):

CURRENT External: 1 A @ 10 V, 330 mA @ 30 V; POT: 500 mA

External: 10 - 30 VDC: POT: 5 VDC +/- 10% INPUT VOLTAGE

ENVIRONMENTAL

AMBIENT LIGHT

DROP RESISTANCE ESD PROTECTION (AIR DISCHARGE) **HUMIDITY (NON-CONDENSING)** PARTICULATE AND WATER SEALING Immune to light exposure in offices/facilities and direct exposure to sunlight.

Withstands 50 drops from 2.0 m / 6.6 ft to concrete 20 kV 90%

PM8300: IP65; PM8300-D, PM8300-DK: IP64 Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -20 to 70 °C / -4 to 158 °F

INTERFACES

TEMPERATURE

INTERFACES Keyboard Wedge; RS-232; RS-485 BC8060 Only; USB; Wand; Ethernet (Standard, Industrial) in compatibility mode (BC9180-433, BC9180-910)

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE DIMENSIONS

Cradle: 24.0 x 10.8 x 9.5 cm / 9.5 x 4.3 x 3.7 in PM8300: 20.7 x 11.4 x 6.9 cm / 8.1 x 4.5 x 2.7 in

PM8300-D, PM8300-DK: 21.0 x 11.4 x 6.9 cm / 8.3 x 4.5 x 2.7 in

DISPLAY

PM8300-D, PM8300-DK: Display Type: Graphic with backlight; Font Dimensions: User selectable

(4 lines x 16 columns default); Screen Dimensions: 32 x 96 pixels PM8300-D Only: 3-Key Keypad;

PM8300-DK Only: 16-Key Keypad Cradle: 380.0 g / 13.4 oz; WEIGHT Reader: 395.0 g / 13.9 oz

BC8030-433, BC8030-910 Base/Charger Multi-Interface

Multi-Interface/RS-485

BC9180-433, BC9180-910 Base Station/Dual Charger

CHR-PM80 Charger (C-8000)

SBS-PM80 Spare Battery Slot compatible w/BC8060

4-Slots (MC-8000)

RBP-PM80 Removable Battery Pack

Cases/Holsters

■ 11-0138 Heated Holder, 36 VDC; 11-0139 Heated Holder, 24 VDC; 11-0140 Heated Holder, 48 VDC

(not for use with PM8300-D models) HLS-P080 Universal Holster (HLS-8000)

PC-P080, PCD-P080 Protective Case/Belt Holster

(PC-8000)

Mounts/Stands

■ 7-0404 Industrial Take-Up Reel HLD-P080 Desk/Wall Holder

(HLD-8000) STD-P080 Hands Free Stand

(STD-8000) VMK-PM80 Vehicle Mount Kit













DATALOGIC STAR CORDLESS SYSTEM™

Point-to-Point Configuration; Multi-Point Configuration

Effective Radiated Power: 433.92 MHz: <10 mW;

910 MHz: <1 mW

READ RATE (MAXIMUM) READING ANGLE **READING INDICATORS**

LIGHT SOURCE

RESOLUTION (MAXIMUM)

READING PERFORMANCE

PRINT CONTRAST RATIO (MINIMUM)

5 mils: 2.1 to 13.3 cm / 0.8 to 5.2 in

7.5 mils: 3.5 to 24.2 cm / 1.4 to 9.5 in

10 mils: 2.9 to 42.8 cm / 1.1 to 16.8 in

13 mils: 2.3 to 55.1 cm / 0.9 to 21.7 in

20 mils: 6.3 to 78.5 cm / 2.5 to 30.9 in

40 mils: 2.5 to 97.8 cm / 1.0 to 38.5 in

READING RANGES

PM8300

TYPICAL DEPTH OF FIELD Minimum distance determined by symbol length and scan angle.

Printing resolution, contrast, and ambient light dependent.

Aiming: 630 - 680 nm VLD, Activated by 'Double-

Pitch: 5 to 55° / -5 to -55°; Roll (Tilt): +/- 20°;

Read Feedback: Datalogic 'Green Spot' on the

PM83X0 Auto Range: 0.190 mm / 7.5 mils

Code, Dual Good Read LEDs; Good Transmission

Beeper; Datalogic Three Green Lights (3GL™) Good

PM8300 AR

7.5 mils: 7.0 to 46.5 cm / 2.7 to 18.3 in 10 mils: 10.8 to 99.9 cm / 4.2 to 39.3 in 13 mils: 12.7 to 147.3 cm / 5.0 to 58.0 in 20 mils: 7.0 to 215.9 cm / 2.7 to 85.0 in 40 mils: 16.0 to 340.0 cm / 6.3 to 133.8 in 55 mils: 0.2 to 4.1 m / 0.7 to 13.5 ft

Reflective - 100 mils: 1.5 to 12.5 m / 4.9 to 41.0 ft

SAFETY & REGULATORY

AGENCY APPROVALS

ENVIRONMENTAL COMPLIANCE LASER CLASSIFICATION

regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. Complies to EU RoHS Caution Laser Radiation - Do not stare into beam

The product meets necessary safety and

CDRH Class II; IEC 60825-1 Class 2

UTILITIES

DATALOGIC ALADDIN¹⁷

Datalogic Aladdin configuration program is available for download at no charge.

WARRANTY

WARRANTY 3-Year Factory Warranty

KEYPAD

- BC8060-433, BC8060-910 Base/Charger



■ FBP-PM80 Fixed Battery Pack (FBP-8000)

- MC-P080 Multiple Battery Charger,
- (RBP-8000)





Item number	Description
PM8300-433K3	PowerScan PM8300, 433 MHz, Kit, KBW (Kit incl. Laser Scanner, BC8030-433MHZ base station, Cable CAB-436, Power Supply, Power cord with European line cord)
PM8300-433K2	PowerScan PM8300, 433 MHz, Kit, RS-232 (Kit incl. Laser Scanner, BC8030-433MHZ base station, Cable CAB-433, Power Supply with European line cord)
PM8300-DKAR- 433RK20	PowerScan PM8300, 433 MHz, Kit, RS-232, Laser Scanner, Auto Range, Display/16-Key Keypad, Removable Battery (Kit inc. Laser Scanner, BC8030-433 Base Station, Cable CAB-433, Power Supply and European line cord)
PM8300-DK433RK20	PowerScan PM8300, 433 MHz, Kit, RS-232, Laser Scanner, Standard Range, Display/16-Key Keypad, Removable Battery (Kit inc. Laser Scanner, BC8030-433 Base Station, Cable CAB-433, Power Supply and European line cord)
PM8300-433K1	PowerScan PM8300, 433 MHz, Kit, USB (Kit incl. Laser Scanner, BC8030-433MHZ base station, Cable CAB-438, Power Supply, Power cord with European line cord)
PM8300-DKAR- 433RK10	PowerScan PM8300, 433 MHz, Kit, USB, Laser Scanner, Auto Range, Display/16-Key Keypad, Removable Battery (Kit inc. Laser Scanner, BC8030-433 Base Station, Cable CAB-438, Power Supply and European line cord)
PM8300-DK433RK10	PowerScan PM8300, 433 MHz, Kit, USB, Laser Scanner, Standard Range, Display/16-Key Keypad, Removable Battery (Kit-Laser Scanner, BC8030-433 Base Station, Cable CAB-438, Power Supply and European Line Cord)
PM8300-D433RBK10	PowerScan PM8300, 433 Mhz, Kit, with Display, Removable Battery, USB kit with Base Station BC8060-433Mhz, and Cable CAB-438 Power Supply and European Line Cord)
PM8300-DKAR433RB	PowerScan PM8300, 433 MHz, Laser Scanner, Auto Range, Display/16-Key Keypad, Removable Battery
PM8300-DAR433	PowerScan PM8300, 433 MHz, Laser Scanner, Auto Range, Display/3-Key Keypad
PM8300-DAR433RB	PowerScan PM8300, 433 MHz, Laser Scanner, Auto Range, Display/3-Key Keypad, Removable Battery
PM8300-AR433	PowerScan PM8300, 433 MHz, Laser Scanner, Auto Range, No Display or Keypad
PM8300-AR433RB	PowerScan PM8300, 433 MHz, Laser Scanner, Auto Range, No Display or Keypad, Removable Battery
PM8300-DK433	PowerScan PM8300, 433 MHz, Laser Scanner, Standard Range, Display/16-Key Keypad
PM8300-DK433RB	PowerScan PM8300, 433 MHz, Laser Scanner, Standard Range, Display/16-Key Keypad, Removable Battery
PM8300-D433	PowerScan PM8300, 433 MHz, Laser Scanner, Standard Range, Display/3-Key Keypad
PM8300-D433-C005	PowerScan PM8300, 433 MHz, Laser Scanner, Standard Range, Display/3-Key Keypad, PreScan (Use with BC8030-433-C005)
PM8300-D433RB	PowerScan PM8300, 433 MHz, Laser Scanner, Standard Range, Display/3-Key Keypad, Removable Battery
PM8300-433	PowerScan PM8300, 433 MHz, Laser Scanner, Standard Range, No Display or Keypad
PM8300-433RB	PowerScan PM8300, 433 MHz, Laser Scanner, Standard Range, No Display or Keypad, Removable Battery
PM8300-910K3	PowerScan PM8300, 910 MHz, Kit, KBW (Kit incl. Laser Scanner, BC8030-910MHZ base station, Cable CAB-436, Power Supply, Power cord wi
PM8300-910K2	PowerScan PM8300, 910 MHz, Kit, RS-232 (Kit incl. Laser Scanner, BC8030-910MHZ base station, Cable CAB-433, Power Supply, Power cord





Item number	Description
PM8300-DKAR- 910RK20	PowerScan PM8300, 910 MHz, Kit, RS-232, Laser Scanner, Auto Range, Display/16-Key Keypad, Removable Battery (Kit inc. Laser Scanner, BC8030-910 Base Station, Cable CAB-433, Power Supply and US Line Cord)
PM8300-DK910RK20	PowerScan PM8300, 910 MHz, Kit, RS-232, Laser Scanner, Standard Range, Display/16-Key Keypad, Removable Battery (Kit incl. Laser Scanner, BC8030-910 Base Station, Cable CAB-433, Power Supply and US Line Cord)
PM8300-910RBK2	PowerScan PM8300, 910 MHz, Kit, RS-232, Removable Battery (Kit incl. Laser Scanner, BC8060-910MHZ base station, Cable CAB-433, Power Supply and US Line Cord)
PM8300-D910RBK2	PowerScan PM8300, 910 MHz, Kit, RS-232, Removable Battery with Display (Kit incl. Laser Scanner BC8060-910MHZ base station, Cable CAB-433, Power Supply and US Line Cord)
PM8300-910K1	PowerScan PM8300, 910 MHz, Kit, USB (Kit incl. Laser Scanner, BC8030-910MHZ base station, Cable CAB-438 Power Supply, with US Line Cord)
PM8300-DKAR- 910RK10	PowerScan PM8300, 910 MHz, Kit, USB, Laser Scanner, Auto Range, Display/16-Key Keypad, Removable Battery (Kit inc. Laser Scanner, BC8030-910 Base Station, Cable CAB-438, Power Supply and US Line Cord)
PM8300-DK910RK10	PowerScan PM8300, 910 MHz, Kit, USB, Laser Scanner, Standard Range, Display/16-Key Keypad, Removable Battery (Kit inc. Laser Scanner, BC8030-910 Base Station, Cable CAB-438, Power Supply and US Line Cord)
PM8300-910RBK1	PowerScan PM8300, 910 MHz, Kit, USB, Removable Battery (Kit incl. Laser Scanner, BC8060-910MHZ base station, Cable CAB-438, Power Supply with US Line Cord)
PM8300-D910RBK1	PowerScan PM8300, 910 MHz, Kit, USB, Removable Battery with Display (Kit incl. BC8060-910MHZ base station, Cable CAB-438, Power Supply with US Line Cord)
PM8300-DKAR910RB	PowerScan PM8300, 910 MHz, Laser Scanner, Auto Range, Display/16-Key Keypad, Removable Battery
PM8300-DAR910	PowerScan PM8300, 910 MHz, Laser Scanner, Auto Range, Display/3-Key Keypad
PM8300-DAR910RB	PowerScan PM8300, 910 MHz, Laser Scanner, Auto Range, Display/3-Key Keypad, Removable Battery
PM8300-AR910	PowerScan PM8300, 910 MHz, Laser Scanner, Auto Range, No Display or Keypad
PM8300-AR910RB	PowerScan PM8300, 910 MHz, Laser Scanner, Auto Range, No Display or Keypad, Removable Battery
PM8300-DK910	PowerScan PM8300, 910 MHz, Laser Scanner, Standard Range, Display/16-Key Keypad
PM8300-DK910RB	PowerScan PM8300, 910 MHz, Laser Scanner, Standard Range, Display/16-Key Keypad, Removable Battery
PM8300-D910	PowerScan PM8300, 910 MHz, Laser Scanner, Standard Range, Display/3-Key Keypad
PM8300-D910-C005	PowerScan PM8300, 910 MHz, Laser Scanner, Standard Range, Display/3-Key Keypad, PreScan (Use with BC8030-910-C005)
PM8300-D910RB	PowerScan PM8300, 910 MHz, Laser Scanner, Standard Range, Display/3-Key Keypad, Removable Battery
PM8300-910	PowerScan PM8300, 910 MHz, Laser Scanner, Standard Range, No Display or Keypad
PM8300-910RB	PowerScan PM8300, 910 MHz, Laser Scanner, Standard Range, No Display or Keypad, Removable Battery
BC8030-433	PowerScan PM8000, 433 MHz, Base Station/Charger, BC-8030, Multi-Interface





Item number	Description
BC8030-433-C005	PowerScan PM8000, 433 MHz, Base Station/Charger, BC-8030, Multi-Interface, PreScan (Use with PM8300-D433-C005)
BC8060-433	PowerScan PM8000, 433 MHz, Base Station/Charger, BC-8060, Multi-Interface/RS-485
BC8030-910	PowerScan PM8000, 910 MHz, Base Station/Charger, BC-8030, Multi-Interface
BC8030-910-C005	PowerScan PM8000, 910 MHz, Base Station/Charger, BC-8030, Multi-Interface, PreScan (Use with PM8300-D910-C005)
BC8060-910	PowerScan PM8000, 910 MHz, Base Station/Charger, BC-8060, Multi-Interface/RS-485

Accessories

Item number	Description
MC-P080	Battery Charger, 4-Slot, MC-8000; (requires the 94ACC4595 power supply)
FBP-PM80	Battery Pack, Fixed, FBP-8000
FBP-PM80-MAG	Battery Pack, Fixed, FBP-8000 with Magnet
RBP-PM80	Battery Pack, Removable, RBP-8000
CHR-PM80	Charging Only Base Station, C-8000
SBS-PM80	Spare Battery Slot, SBS-8000 (use with BC8060 or CHR-PM80 models)
90A051950	CAB-428 RS485 Interface Splitter
CAB-485	Cable, KBW 3151, 347x, 378x, Coiled, CAB-485, 11 ft.
CAB-437	Cable, KBW, PS/2, Coiled, CAB-437, 9 ft.
CAB-463	Cable, KBW, PS/2, Laptop, Coiled, 3.6 m, CAB-463
CAB-462	Cable, KBW, PS/2, PWR, Coiled 3.6 m, CAB-462
CAB-436	Cable, KBW, PS/2, Straight, CAB-436, 6 ft.
CAB-474	Cable, RS-232 PWR, 25P, Female, Coiled, 3.6 m, CAB-474
CAB-477	Cable, RS-232 PWR, 25P, Female, Coiled, 7.6 m, CAB-477
CAB-459	Cable, RS-232 PWR, 9P, Female, Coiled, 3.6 m, CAB-459
CAB-434	Cable, RS-232 PWR, 9P, Female, Coiled, CAB-434, 8 ft.
CAB-433	Cable, RS-232 PWR, 9P, Female, Straight, CAB-433, 6 ft.
CAB-471	Cable, RS-232, 25P, Female, Coiled, CAB-471, 10 ft.
CAB-509	Cable, RS-232, 25P, Male, CBX800, External Power, Coil, 12 ft
CAB-472	Cable, RS-232, 25P, Male, Coiled, CAB-472, 10 ft.
CAB-479	Cable, RS-232, 9D, Female, POT, Coiled, 25 ft, 90A052014, CAB-479
CAB-456	Cable, RS-232, 9P, Male, Coiled, 3.6 m, CAB-456
CAB-450	Cable, RS-232, Motorola VRC 69xx, CAB-450, 12 ft.





Accessories

Item number	Description
CAB-451	Cable, RS-232, Motorola VRS 79/89xx, CAB-451, 6 ft.
CAB-467	Cable, USB, Type A, Coiled, 3.6 m, CAB-467, 12 ft.
CAB-524	Cable, USB, Type A, Coiled, POT, CAB-524, 8 ft.
CAB-465	Cable, USB, Type A, Straight, 3.6 m, CAB-465
CAB-438	Cable, USB, Type A, Straight, CAB-438, 6.5 ft.
CAB-490	Cable, WE, 9P, Female, Coiled, 4.6 m, CAB-490
CAB-473	Cable, WE, 9P, Male, Coiled, 8 ft, DP9000
CAB-470	Cable, WE, 9P, Male, Straight, CAB-470, 6.5 ft.
CAB-489	Cable, WE, Lemo, LXE Terminal, Coiled, 2.4 m, CAB-489
CAB-491	Cable, WE, RJ10 Intermec 2010, 2.4 m, CAB-491
CAB-488	Cable, WE, RJ6 Decathlon, Coiled, 6.1 m, CAB-488
CAB-487	Cable, WE, RJ6, Male, Coiled, 2.4 m, CAB-487
HLD-P080	Holder, Desk/Wall Mount
11-0139	Holder, Heated, 24VDC (Not for use with display models)
11-0138	Holder, Heated, 36VDC (Not for use with display models)
11-0140	Holder, Heated, 48VDC (Not for use with display models)
PC-P080	Protective Case/Belt Holster, PC-8000 (for unit without display)
PCD-P080	Protective Case/Belt Holster, PC-8000-D (for unit with display)
7-0404	Industrial Take Up Reel
90ACC1876	Mounting Plate, Metal for STD-xxxx
STD-P080	Stand, Hands-free, STD-8000
891000098	Tether Hook, PowerScan 8xxx, No Display, Qty 5
VMK-8000	Vehicle Mount Kit, VMK-8000
90ACC1885	Power Cord, 2-Pin, EU
90ACC1887	Power Cord, 2-Pin, UK
90ACC1886	Power Cord, 2-Pin, US
94ACC4595	Power Supply without power cord (3 pin)
90ACC1883	Power Supply, 12VDC, PG12-10P55 (For Use with 90ACCXXXX Power Cords Sold Separately)
90ACC1920	Power Supply, 12VDC, US, PG12-10P55-US (includes power cord 90ACC1886)





Service Agreements

Item number	Description
41415-80	MINIMUM REPAIR CHARGE, PM8300
42311-80	MINIMUM REPAIR CHARGE, PS 83XX M AR
Q-PM83-R	PowerScan 8300M/BT EofC Overnight Replacement Comprehensive, 1 Year Renewal
Q-PM83-3	PowerScan 8300M/BT EofC Overnight Replacement Comprehensive, 3 Years
Q-PM83-5	PowerScan 8300M/BT EofC Overnight Replacement Comprehensive, 5 Years
W-PM83-R	PowerScan 8300M/BT EofC 2 Days Comprehensive, 1 Year Renewal
W-PM83-3	PowerScan 8300M/BT EofC 2 Days Comprehensive, 3 Years
W-PM83-5	PowerScan 8300M/BT EofC 2 Days Comprehensive, 5 Years
E-PM83-R	PowerScan 8300M/BT EofC 5 Days, 1 Year Renewal
E-PM83-3	PowerScan 8300M/BT EofC 5 Days, 3 Years
E-PM83-5	PowerScan 8300M/BT EofC 5 Days, 5 Years
W-PM83A-R	PowerScan 8300M-AR EofC 2 Days Comprehensive, 1 Year Renewal
W-PM83A-3	PowerScan 8300M-AR EofC 2 Days Comprehensive, 3 Years
W-PM83A-5	PowerScan 8300M-AR EofC 2 Days Comprehensive, 5 Years
E-PM83A-R	PowerScan 8300M-AR EofC 5 Days, 1 Year Renewal
E-PM83A-3	PowerScan 8300M-AR EofC 5 Days, 3 Years
E-PM83A-5	PowerScan 8300M-AR EofC 5 Days, 5 Years
Q-PM83A-R	PowerScan 8300M-AR EofC Overnight Replacement Comprehensive, 1 Year Renewal
Q-PM83A-3	PowerScan 8300M-AR EofC Overnight Replacement Comprehensive, 3 Years
Q-PM83A-5	PowerScan 8300M-AR EofC Overnight Replacement Comprehensive, 5 Years
W-PM83-16-R	PowerScan 8300M-DK EofC 2 Days Comprehensive, 1 Year Renewal
W-PM83-16-3	PowerScan 8300M-DK EofC 2 Days Comprehensive, 3 Years
W-PM83-16-5	PowerScan 8300M-DK EofC 2 Days Comprehensive, 5 Years
E-PM83-16-R	PowerScan 8300M-DK EofC 5 Days, 1 Year Renewal
E-PM83-16-3	PowerScan 8300M-DK EofC 5 Days, 3 Years
E-PM83-16-5	PowerScan 8300M-DK EofC 5 Days, 5 Years
Q-PM83-16-R	PowerScan 8300M-DK EofC Overnight Replacement Comprehensive, 1 Year Renewal
Q-PM83-16-3	PowerScan 8300M-DK EofC Overnight Replacement Comprehensive, 3 Years
Q-PM83-16-5	PowerScan 8300M-DK EofC Overnight Replacement Comprehensive, 5 Years
W-BC8-R	PowerScan 8x00M/BT Base Station EofC 2 Days Comprehensive, 1 Year Renewal
W-BC8-3	PowerScan 8x00M/BT Base Station EofC 2 Days Comprehensive, 3 Years
W-BC8-5	PowerScan 8x00M/BT Base Station EofC 2 Days Comprehensive, 5 Years





Service Agreements

Item number	Description
E-BC8-R	PowerScan 8x00M/BT Base Station EofC 5 Days, 1 Year Renewal
E-BC8-3	PowerScan 8x00M/BT Base Station EofC 5 Days, 3 Years
E-BC8-5	PowerScan 8x00M/BT Base Station EofC 5 Days, 5 Years
Q-BC8-R	PowerScan 8x00M/BT Base Station EofC Overnight Replacement Comprehensive, 1 Year Renewal
Q-BC8-3	PowerScan 8x00M/BT Base Station EofC Overnight Replacement Comprehensive, 3 Years
Q-BC8-5	PowerScan 8x00M/BT Base Station EofC Overnight Replacement Comprehensive, 5 Years
41415-71	WHOLE UNIT REPAIR, PM8300
42311-81	WHOLE UNIT REPAIR,PS 83XX M AR

MORE DATALOGIC BARCODE SCANNERS

