

# Zebra LI4278 Barcode Scanners

On the following pages you will find detailed manufacturer information about this product from our TISWARE hardware and software portfolio.

## If you need more information, please contact us!

If you have any questions about or are interested in this or other products from our portfolio, please contact our sales team. Our colleagues are happy to help.

Phone: **+49 2871 2722-0**

E-mail: **contact@tis-gmbh.com**

## Other products from the TIS GmbH portfolio



### TISLOG TELEMATICS SOFTWARE

TISLOG logistics and transport software provides powerful and flexible solutions for mobile order management, capable of exactly what you need for the individual work processes of your business.



[www.tislog.com](http://www.tislog.com)



### TISPLUS HARDWARE ACCESSORIES

TISPLUS - Clever accessories for ergonomic handling on the go and in the warehouse. und im Lager. Development, design and production of our TISPLUS products take place at 100% in Germany.



[www.tisplus.com](http://www.tisplus.com)

### BACKGROUND TIS GMBH

The TIS GmbH, based in Bocholt is one of the market leaders for sophisticated telematics projects. TIS stands for "Technical Information Systems". Since 1985 the company develops intelligent telematics solutions for freight forwarders, transport and logistics companies and retail chains. Currently, more than 50 employees work for TIS. The latest generation of products are the platform-independent software solutions under the brand name TISLOG Logistics & Mobility. Together with the powerful hardware of renowned partners and the in-house developed hardware accessories TISLOG builds the optimal solution for companies looking for professional telematics solutions.



More information on the TIS GmbH and our portfolio of software, hardware and accessories on

[www.tis-gmbh.com](http://www.tis-gmbh.com)

# ZEBRA LI4278

## GENERAL PURPOSE CORDLESS LINEAR IMAGER

The LI4278 takes 1-D bar code scanning to the next level, allowing workers to scan faster and farther. Workers can capture virtually any 1-D bar code including the typical bar codes that are printed on paper labels; electronic bar codes displayed on the screen of a mobile phone, tablet or computer that allows retailers to easily process loyalty cards, mobile coupons and more; and the high density (HD) bar codes commonly used in electronic component manufacturing. 100 percent UPC bar codes can be captured from near contact to over 30 in./76.2 cm away, while 200% UPC codes can be scanned at 55 in./139.7 cm away. Since bar codes can be captured at extreme angles, scanning is easier than ever, so workers spend less time maneuvering the scanner and more time on task. And an optional cradle that enables presentation mode gives your workers the flexibility to use the scanner in handheld and hands-free modes.



### **Cordless Freedom**

Bluetooth frees workers from cords, allowing cashiers to easily scan items inside and outside of the cash wrap. In addition, Bluetooth v2.1 with EDR provides better encryption for improved security; better wireless performance; better energy management to preserve power for a full shift and easy pairing with the host device.

### **Built for All Day Everyday Use**

A patent pending single circuit board improves reliability by eliminating interconnections. Superior battery power management delivers the largest number of scans per battery charge to support scan intensive applications. You can use it in dusty and wet environments. The scan line is easy to see outdoors in bright sunlight as well as indoors in dim lighting. It can survive drops to concrete. And both cradles can handle over a quarter million insertions.

### **Cost Effective Upgrade Path**

The LI4278 provides a positive return on investment by utilizing the same existing cradles and accessories as its cousins, the LS4278 and DS6878. Current investments are preserved, yet you can easily migrate to the latest in scanning technology.

### **Maximum Uptime For A Low Tco**

Remote management tools combine with industry leading all-inclusive affordable service plans to keep devices in the hands of your workforce practically every minute of every working day. Service from the Start Advance Exchange Support provides next-business-day replacement of devices that require repair. Built-in Comprehensive Coverage protects your scanners from the unexpected, significantly reducing unforeseen repair expenses and delivering service peace of mind from the moment you purchase the device.

## Features

### **Excellent 1-D Scanning Performance**

Delivers superior scanning speed and a wide data capture range.

### **Captures Virtually All 1-D Bar Codes on any Surface Including Mobile Phone Displays**

Capture bar codes printed on traditional paper labels or displayed on the screen of a mobile phone, tablet or computer.

### **Wide Working Range**

Reads UPC bar codes from 1 in./2.54 cm to over 30 in./76.2 cm as well as high density codes and extended ranges for greater application flexibility.

### **Superior Motion and Angular Tolerance**

Bar codes can be captured faster, and there is no need to pause between scans.

### **Patent Pending Single Circuit Board Construction**

Maximizes durability and reduces downtime.

### **Bright Crisp Aiming Line**

Easier to aim in bright or dim lighting environments.

### **Built-in Rechargeable Replaceable Battery**

Provides largest number of scans per charge well beyond a single shift in the highest usage profiles; replaceable battery ensures long lifecycle.

### **Long Life Industrial Charging Contacts**

Reliable performance, rated to 250,000+ insertions.

### **Compatible with 123Scan and Remote Scanner Management (RSM)**

Dramatically reduces management time and cost, from initial configuration to day-to-day management; SDK available for custom development.

### **Withstands 100+ Consecutive Drops to Concrete**

Protects against downtime from breakage due to everyday drops.

### **Multi Point-to-Point**

Use up to three scanners with a single desktop cradle and seven scanners with a presentation cradle, reducing capital expenditures and maintenance costs.

**THE NEXT GENERATION IN 1-D SCANNING.**

For more information, please visit us on the web at [www.zebra.com/li4278](http://www.zebra.com/li4278)  
or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact)

## PRODUCT SPEC SHEET

ZEBRA LI4278

### Batch Mode Operation

Allows user to continue scanning outside communications range; can scan over 500 UPC bar codes into memory and upload automatically when in communication range.

### Flexible Mounting Vertical or Horizontal

Desktop cradle provides versatility to accommodate your unique environment.

### Bluetooth 2.1

Provides better security, better performance, better energy management and much easier pairing over the Bluetooth wireless connection.

### Backward Compatible

Works with LS4278 cradles, providing a very cost-effective upgrade path.

# LI4278 Specifications

PERFORMANCE CHARACTERISTICS	
Skew Tolerance	±65°
Pitch Tolerance	±65°
Roll Tolerance	±45°
Scan Pattern	Single bright aiming line
Scan Angle	Horizontal 35°
Scan Speed	547 scans per second
Motion Tolerance	25 in./ 63.5 cm per second
Light Source	LED Class 1 device 617nm (amber)
Min. Print Contrast	15% MRD
Scans Per Charge	Up to 57,000
Hours of Operation	Per full charge: 72 hours
UTILITIES	
123Scan, Remote Scanner Management (RSM), Scanner Management Services (SMA), Zebra Scanner SDK	
USER ENVIRONMENT	
Ambient Light Immunity	Max 108,000 lux
Operating Temp.	32° F to 122° F/ 0° C to 50° C
Storage Temperature	-40° F to 158° F/-40° C to 70° C
Humidity	5% to 85% RH, non-condensing
Drop Specification	Over 100 drops at 5 ft./1.5 m at room temperature; survives 6ft./1.8 m drops to concrete
Environmental Sealing	Gasket sealed housing withstands dust and can be sprayed clean
Bar Code Symbolologies	UPC/EAN: UPC-A, UPC-E, UPC-E1, EAN-8/JAN 8, EAN-13/JAN 13, Bookland EAN, Bookland ISBN Format, UCC Coupon Extended Code, ISSN EAN Code 128 Including GS1-128, ISBT 128, ISBT Concatenation, Code 39 including Trioptic Code 39, Convert Code 39 to Code 32 (Italian Pharmacy Code), Code 39 Full ASCII Conversion Code 93 Code 11 Matrix 2 of 5 Interleaved 2 of 5 (ITF) Discrete 2 of 5 (DTF) Codabar (NW - 7) Chinese 2 of 5 IATA Inverse 1-D (except all GS1 DataBars) GS1 DataBar including GS1 DataBar-14, GS1 DataBar Limited, GS1 DataBar Expanded

WIRELESS CONNECTIVITY	
Radio	Bluetooth v2.1 Class 2 Radio
Data Rate	3.0 Mbit/s (2.1 Mbit/s) Bluetooth v2.1
Radio Range*	330 ft./100 m (line of sight)
*Using presentation cradle configuration	
PHYSICAL CHARACTERISTICS	
Dimensions	3.84 in. H x 2.75 in. W x 7.34 in. L 9.8 cm H x 7 cm W x 18.6 cm L
Weight	7.9 oz./224 grams
Cradle Interface	RS232, RS485 (IBM), USB, Keyboard Wedge
Color	Black; White
Battery	Rechargeable replaceable battery with 'green sustainability'
DECODE RANGES (TYPICAL WORKING RANGES**)	
3 mil	Minimum resolution
4 mil	4-10 in./10.2-25.4 cm
5 mil	3-13 in./7.6-33 cm
7.5 mil	1.5-19 in./3.8-48.3 cm
13 mil (100% UPC-A)	1-31 in./2.5-78.7 cm
20 mil	1-42 in./2.5-106.7 cm
26 mil (200% UPC-A)	3-55 in./7.6-140 cm
100 mil (paper)	>20 ft./6 m
** Ranges are calculated on Code 39 unless otherwise noted	
REGULATORY	
Technical Requirements	EMC FCC Part 15 Class B, ICES 003 Class B, IEC 60601-1-2 Environmental RoHS Directive 2002/95/EEC Electrical Safety C22.2 No. 60950-1, EN 60950-1, IEC 60950-1, UL 60950-1 LED Class 1
Environmental	RoHS Compliant
WARRANTY	
Subject to the terms of Zebra's hardware warranty statement, the LI4278 is warranted against defects in workmanship and materials for a period of 36 months from the date of shipment. For the complete Zebra hardware product warranty statement, go to: <a href="http://www.zebra.com/warranty">http://www.zebra.com/warranty</a>	

Specifications subject to change without notice.



NA and Corporate Headquarters  
+1 800 423 0442  
inquiry4@zebra.com

Asia-Pacific Headquarters  
+65 6858 0722  
contact.apac@zebra.com

EMEA Headquarters  
zebra.com/locations  
mseurope@zebra.com

Latin America Headquarters  
+1 847 955 2283  
la.contactme@zebra.com

## Zebra LI4278 Barcode Scanners

Item numbers	Description
LI4278-PRBU2100AAR	LI4278 Black Presentation Cradle USB (No Line Cord) Kit - APAC: LI4278-SR20007WR Scanner, CBA-U21-S07ZAR Shielded USB Cable, CR0078-PC1F007WR Cradle, PWRS-14000-148R Power Supply, Line Cord Not Included
LI4278-PRBU2100AWR	LI4278 Black Presentation Cradle USB (No Line Cord) Kit: LI4278-SR20007WR Scanner, CBA-U21-S07ZAR Shielded USB Cable, CR0078-PC1F007WR Cradle, PWRS-14000-148R Power Supply, Line Cord Not Included
LI4278-PRWU2100AAR	LI4278 White Presentation Cradle USB (No Line Cord) Kit - APAC: LI4278-SR20001WR Scanner, CBA-U21-S07ZAR Shielded USB Cable, CR0078-PC1F007WR Cradle, PWRS-14000-148R Power Supply, Line Cord Not Included
LI4278-PR-WU2100AWR	LI4278 White Presentation Cradle USB (No Line Cord) Kit: LI4278-SR20001WR Scanner, CBA-U21-S07ZAR Shielded USB Cable, CR0078-PC1F007WR Cradle, PWRS-14000-148R Power Supply, Line Cord Not Included
LI4278-SR1R0110SRN	LI4278-SR White Standard Cradle Serial KIT - NA: LI4278-SR20001WR Scanner, CBA-R01-S07PAR Serial Cable, CR0078-SC10001WR Cradle, PWRS-14000-253R Power Supply (USA, CA, MX, JP, TW)
LI4278-SR7R0110SRN	LI4278-SR Black Standard Cradle Serial KIT - NA: LI4278-SR20007WR Scanner, CBA-R01-S07PAR Serial Cable, CR0078-SC10007WR Cradle, PWRS-14000-253R Power Supply (USA, CA, MX, JP, TW)
LI4278-TRBU0100ZAR	LI4278 Black Standard Cradle USB Kit - APAC: LI4278-SR20007WR Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10007WR Cradle
LI4278-TRBU0100ZER	LI4278 Black Standard Cradle USB Kit - EMEA: LI4278-SR20007WR Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10007WR Cradle
LI4278-TRBU0100ZLR	LI4278 Black Standard Cradle USB Kit - Latin America: LI4278-SR20007WR Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10007WR Cradle
LI4278-TRBU0100ZWR	LI4278 Black Standard Cradle USB Kit: LI4278-SR20007WR Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10007WR Cradle
LI4278-TRBU0100ZY	LI4278 Black Standard Cradle USB KIT - INDIA ONLY: LI4278-SR20007Y Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10007WR Cradle
LI4278-TRWU0100ZAR	LI4278 White Standard Cradle USB Kit - APAC: LI4278-SR20001WR Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10001WR Cradle
LI4278-TRWU0100ZER	LI4278 White Standard Cradle USB Kit - EMEA: LI4278-SR20001WR Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10001WR Cradle
LI4278-TRWU0100ZLR	LI4278 White Standard Cradle USB Kit - Latin America: LI4278-SR20001WR Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10001WR Cradle
LI4278-TR-WU0100ZWR	LI4278 White Standard Cradle USB Kit: LI4278-SR20001WR Scanner, CBA-U01-S07ZAR USB Cable, CR0078-SC10001WR Cradle
LI4278-SR20001WR	LI4278: Cordless Linear Imager, Bluetooth, Cash Register White
LI4278-SR20007WR	LI4278: Cordless Linear Imager, Bluetooth, Twilight Black
LI4278-SR20007Y	LI4278: Linear Imager, Standard Range, Cordless, Twilight Black - INDIA ONLY

## Accessories

Item numbers	Description
BTRY-LS42RAA0E-01	Spare Battery – DS6878/LI4278/LS4278
11-66553-06R	Wall Mount holder
CBA-S01-S07ZAR	Synapse Adapter Cable: 7ft. Straight. Cable Code S01
CBA-S03-C09ZAR	Synapse Adapter Cable: 9ft. Coiled. Cable Code S03
CBA-S04-C16ZAR	Synapse Adapter Cable: 16ft. Coiled
CBA-S05-S09EAR	Synapse Adapter Cable with EAS 9ft. Straight. Cable Code S05
CBA-M01-S07ZAR	Cable - IBM: 468x/9x, 7ft (2m) Straight, Port 9B
CBA-M04-S07ZAR	Cable - IBM: 468x/9x, 7ft (2m) Straight, Port 5B
CBA-M02-C09ZAR	Cable - IBM: 468x/9x, 9ft (2.8m) Coiled, Port 9B
CBA-M03-S09EAR	Cable - IBM: 468x/9x, 9ft (2.8m) Straight, Port 9B with EAS
CBA-M10-C12ZAR	Cable - IBM: 468x/9x, 12ft (3.7m) Coiled, Port 9B
CBA-M11-C20ZAR	Cable - IBM: 468x/9x, 12ft (6m) Coiled, Port 9B
CBA-K01-S07PAR	Cable - Keyboard Wedge: 7ft. (2m) Straight, PS/2 Power Port
CBA-K02-C09PAR	Cable - Keyboard Wedge: 9ft. (2.8m) Coiled, PS/2 Power Port
CBA-K05-S15PAR	Cable - Keyboard Wedge: 15ft (4.6m) Straight, PS/2 Power Port
CBA-K06-C12PAR	Cable - Keyboard Wedge: 12ft. (3.7m) Coiled, PS/2 Power Port
CBA-K08-C20PAR	Cable - Keyboard Wedge: 20ft. (6m) Coiled, PS/2 Power Port
CBA-D02-C09ZAR	Cable - Scanner Emulation: 9ft. (2.8m) Coiled, Undecoded
CBA-W01-S07ZAR	Cable - Wand: 7ft. (2m) Straight
CBA-W02-C09ZAR	Cable - Wand: 9ft. (2.8m) Coiled
CBA-R01-S07PAR	Cable - RS232: DB9 Female Connector, 7ft. (2m) Straight, TxD on 2
CBA-R02-C09PAR	Cable - RS232: DB9 Female Connector, 9ft. (2.8m) Coiled, TxD on 2
CBA-R28-C09ZAR	Cable - RS232: 9ft. (2.8m) Coiled, Verifone Ruby
CBA-R31-C09ZAR	Cable - RS232: 9 ft. (2.8m) Coiled, NCR 7448
CBA-R37-C09ZAR	Cable - RS232: DB9 Female Connector, 9ft (2.8m) Coiled, Power Pin 9
CBA-R03-C12PAR	Cable - RS232: DB9 Female Connector, 12ft. (3.6m) Coiled, TxD on 2
CBA-R06-C20PAR	Cable - RS232: DB9 Female Connector, 20ft. (6m) Coiled, TxD on 2
CBA-R08-S07ZAR	Cable - RS232: 7ft. (2m) Straight, Nixdorf Beetle- 5V Direct Power
CBA-R09-C09ZAR	Cable - RS232: 9ft. (2.8m) Coiled, Nixdorf Beetle- 5V Direct Power
CBA-R10-S07ZAR	Cable - RS232: 7ft. (2m) Straight, Nixdorf Beetle- Direct Power
CBA-R11-C09ZAR	Cable - RS232: 9ft. (2.8m) Coiled, Nixdorf Beetle- Direct Power
CBA-R12-C12ZAR	Cable - RS232: 12ft. (3.7m) Coiled, Nixdorf Beetle- Direct Power

## Accessories

Item numbers	Description
CBA-R13-S09EAR	Cable - RS232: 9ft. (2.8m) Straight, Nixdorf Beetle- Direct Power with EAS.
CBA-R22-C09ZAR	Cable - RS232: 9ft (2.8m) Coiled, Fujitsu T POS 500 ICL
CBA-R23-S07ZBR	Cable - RS232: 7Ft (2M) Straight, Fujitsu T Pos 500 Icl, With Ttl Current Limit Protection
CBA-R24-C20ZAR	Cable - RS232: 20ft (6m) Coiled, Fujitsu T POS 500 ICL
CBA-R32-S07PAR	Cable - RS232: DB9 Female Connector, 7ft. (2m) Straight, TxD on 2, True Converter
CBA-R41-S12ZAR	Cable - RS232: 12ft. (3.7m) Straight, Nixdorf Beetle- Direct Power
CBA-U21-S07ZAR	Cable - Shielded USB: 7ft. (2.8m), Straight
CBA-U23-S07ZAR	Cable - Shielded USB: Power Plus Connector, 7ft. (2.8m), Straight
CBA-U27-S09EAR	Cable - Shielded USB: Power Plus Connector, 9ft. (2.8m), Straight, EAS
CBA-U29-C15ZAR	Cable - Shielded USB: Series A Connector, 15ft. (4.6m), Coiled
CBA-U30-S15ZAR	Cable - Shielded USB: 15ft. (4.6m), Straight
CBA-U32-C09ZAR	Cable - Shielded USB: Series A Connector, 9ft. (2.8m), Coiled
CBA-U26-S09EAR	Cable - Shielded USB: Series A Connector, 9ft. (2.8m), Straight, EAS
CBA-U28-C15ZAR	Cable - Shielded USB: Power Plus Connector, 15ft. (4.6m), Coiled
CBA-U34-C09ZAR	Cable - Shielded USB: Power Plus Connector, 9ft. (2.8m), Coiled
CBA-U35-S15ZAR	Cable - Shielded USB: Power Plus Connector, 15ft. (4.6m), Straight
CBA-U01-S07ZAR	Cable - USB: Series A Connector, 7ft. (2m) Straight
CBA-U03-S07ZAR	Cable - USB: Power Plus Connector, 7ft. (2m) Straight
CBA-U08-C15ZAR	Cable - USB: Power Plus Connector, 15ft. (4.6m) Coiled
CBA-U09-C15ZAR	Cable - USB: Series A Connector, 15ft. (4.6m) Coiled
CBA-U10-S15ZAR	Cable - USB: Series A Connector, 15ft. (4.6m) Straight
CBA-U12-C09ZAR	Cable - USB: Series A Connector, 9ft. (2.8m) Coiled
CBA-U15-S15ZAR	Cable - USB: Power Plus Connector, 15ft. (4.6m) Straight
CBA-U06-S09EAR	Cable - USB: Series A Connector, 9ft. (2.8m) Straight, with EAS
CBA-U14-C09ZAR	Cable - USB: Power Plus Connector, 9ft. (2.8m) Coiled
CR0078-PC1F007WR	Presentation Base, Charging, Bluetooth™, Twilight Black; (Requires 12V Power Supply, PWRS-14000-148R and a country specific power cord to be ordered separately; USB Cable must be Shielded Type)
CR0078-SC10001WR	Standard Base Cradle, Bluetooth, charging, cash register white; USB cable must be unshielded type. NOT FOR USE IN HEALTHCARE ENVIRONMENTS. IN HEALTHCARE ENVIRONMENTS USE CR0078-SC1009BWR.
CR0078-SC10007WR	Standard Base Cradle, Bluetooth, charging, twilight black; USB cable must be unshielded type. NOT FOR USE IN HEALTHCARE ENVIRONMENTS. IN HEALTHCARE ENVIRONMENTS USE CR0078-SC1009BWR.
CR0008-SC10007R	Cradle: Charge Only Base , Twilight Black

## Accessories

Item numbers	Description
50-12500-066	Wrist Lanyard
23844-00-00R	US AC line cord, 7.5 feet long, grounded, three wire for power supplies. Associated Countries: United States.
PWRS-14000-148R	Power Supply:100-240 VAC,12VDC,4.16A. Order country specific three wire grounded AC Line Cord separately.
PWRS-14000-253R	Power Supply: 5VDC,850MA, US-CA-MX-JP-TW
50-14000-259R	Power Supply: 5VDC,850MA, ARGENTINA-UY
PWRS-14000-254R	Pwr Sply: 5Vdc,850Ma, India Adapter Plug.
PWRS-14000-255R	Power Supply: 5VDC, 850MA, Brazil/Korea, Must order line cord separately
PWRS-14000-256R	Power Supply: 5VDC,850MA, EU-UK-EMEA-RU-ZA
PWRS-14000-257R	Power Supply: 5VDC,850MA, CHINA
PWRS-14000-258R	Power Supply:5VDC,850MA, AU-HK-NZ

## Service Agreements

Item numbers	Description
SCE-LI4278-10	1 Year Zebra OneCare Service Center Essential. Does not include Comprehensive Coverage. Includes coverage for cradle.
SCS-LI4278-10	1 Year Zebra OneCare Service Center Select. Includes Comprehensive Coverage. Includes coverage for cradle. Check datasheet for regional availability.
SSB-LI4278-20-R	2 Year Service from the Start Service Center Bronze Renewal. Does not include Comprehensive Coverage. Includes coverage for cradles. Can only be ordered ONCE after initial Service from the Start contract expires
SSE-LI4278-20-R	2 Year Zebra OneCare Essential Renewal. Includes Comprehensive Coverage. Includes coverage for cradles. Can only be ordered ONCE after initial Zebra OneCare contract expires
SSE-LI4278-30	3 Year Zebra OneCare Essential. Includes Comprehensive Coverage. Includes coverage for cradles.
SSS-LI4278-20-R	2 Year Zebra OneCare Select Renewal. Includes Comprehensive Coverage. Includes coverage for cradle. Check datasheet for regional availability. Can only be ordered ONCE after initial Zebra OneCare contract expires
SSS-LI4278-30	3 Year Zebra OneCare Select. Includes Comprehensive Coverage. Includes coverage for cradle. Check datasheet for regional availability.
SWS-EMTS-10	1-Yr software technical support for non-Windows OS-based ADC devices. Price is per device. Not for wireless infrastructure, RFID, or MCD products. Does not include the MP6XXX products
SWS-EMTS-30	3-Yr software technical support for non-Windows OS-based ADC devices. Price is per device. Not for wireless infrastructure, RFID, or MCD products. Does not include the MP6XXX products
OPT-ADCCOMM-10	1 Year ADC Commissioning Option. Cannot be ordered alone.
OPT-ADCCOMM-20	2 Year ADC Commissioning Option. Cannot be ordered alone
OPT-ADCCOMM-30	3 Year ADC Commissioning Option. Cannot be ordered alone

## Service Agreements

Item numbers	Description
OPT-ADCEXPSHIP-10	1 Year ADC Express Shipping Option. Cannot be ordered alone. Available in NALA only
OPT-ADCEXPSHIP-20	2 Year ADC Express Shipping Option. Cannot be ordered alone. Available in NALA only
OPT-ADCEXPSHIP-30	3 Year ADC Express Shipping Option. Cannot be ordered alone. Available in NALA only
OPT-DASHBOARD-20	2 Year Asset Visibility Dashboard Access. Cannot be ordered alone. Must be purchased together with a Zebra OneCare Essential agreement.
OPT-DASHBOARD-30	3 Year Asset Visibility Dashboard Access. Cannot be ordered alone. Must be purchased together with a Zebra OneCare Essential agreement.

## MORE ZEBRA BARCODE SCANNERS

Zebra offers a whole variety of barcode scanners. Find more models here:

<https://www.zebra.com/us/en/products/scanners.html>

