





Zebra VC80 Forklift Terminal

On the following pages you will find detailed manufacturer information about this product from our TISWARE hardware and software portfolio.

If you need more information, please contact us!

If you have any questions about or are interested in this or other products from our portfolio, please contact our sales team. Our colleagues are happy to help.

Phone: +49 2871 2722-0 E-mail: contact@tis-gmbh.com

Other products from the TIS GmbH portfolio



TISLOG TELEMATICS SOFTWARE

TISLOG logistics and transport software provides powerful and flexible solutions for mobile order management, capable of exactly what you need for the individual work processes of your business.



www.tislog.com



TISPLUS HARDWARE ACCESSORIES

TISPLUS - Clever accessories for ergonomic handling on the go and in the warehouse. und im Lager. Development, design and production of our TISPLUS products take place at 100% in Germany.



www.tisplus.com

BACKGROUND TIS GMBH

The TIS GmbH, based in Bocholt is one of the market leaders for sophisticated telematics projects. TIS stands for "Technical Information Systems". Since 1985 the company develops intelligent telematics solutions for freight forwarders, transport and logistics companies and retail chains. Currently, more than 50 employees work for TIS. The latest generation of products are the platform-independent software solutions under the brand name TISLOG Logistics & Mobility. Together with the powerful hardware of renowned partners and the in-house developed hardware accessories TISLOG builds the optimal solution for companies looking for professional telematics solutions.

More information on the TIS Gmbh and our portfolio of software, hardware and accessories on

www.tis-gmbh.com



VC80 Vehicle Mount Mobile Computer

GET THE FULL WINDOWS SUPPORT YOU NEED TO PUT YOUR DESKTOP APPLICATIONS AT THE FINGERTIPS OF YOUR VEHICLE OPERATORS

With the VC80, you can give operators in material handling vehicles mobile access to the desktop applications they need to complete tasks faster and more accurately. You get full Windows support in a super rugged design built for your toughest indoor and outdoor environments — from warehouses and distribution centers to airports, seaports, railway yards and more — plus the fastest wireless connections available to keep workers connected to your data and productive. And with its compact design and flexible mounting options, it's easy to install in forklifts, clamp trucks, yard mules, cranes and more. The VC80 — real desktop power to handle your mobile application needs.



Freezer-ready for the coldest supply chain

You get true frost and condensation free operation with touchscreen, board and battery heaters, plus smart temperature sensors that automatically control heater and heating speed.

Maximum rugged design

The VC80 is ready for your toughest environments, with dust-and-water tight IP66 sealing, sealed connectors, and extreme temperature, shock and vibration testing.

Easy to see indoors and outside

Choose either 1,000 NITs for a super bright screen that is easy to see outdoors or 400 NITs for indoor operation.

Programmable keys to simplify the most complex operations

With six direct and six soft programmable keys, multi-step processes can be executed with one keypress, boosting throughput and productivity.

Designed for voice in your loudest environments

The very loud front facing speaker and instantly accessible volume control make it easy to hear scanner feedback and app notifications.

Fits in virtually any warehouse/material handling vehicle

Multiple mounting options, including standard RAM mounts combine with a compact size for an easy fit and easy mounting, even in the smallest vehicles. And a 10-second quick release mount makes it easy to move the VC80 to another vehicle during vehicle maintenance or device repair.

Flexible data entry — touch or optional keyboard

The touchscreen's soft keyboard and haptic vibration feedback make it easy to use touch input, even with the thickest gloves. Or you can choose to mount an optional keyboard on the bottom or side of the VC80.

Power to support today's graphics-intensive applications

Get the power you need to deliver blazing speed for your applications with your choice of a dual core 1.33 GHz with 2GB RAM or a quad core 1.91 GHz processor with 4GB RAM.

Superior flexibility — add bar code scanning, voice and more

Different workers need different capabilities. That's why the VC80 offers all the ports you need to add bar code scanners, mobile printers, a push-to-talk microphone and more.

Rock-solid fast Wi-Fi connectivity

With support for the latest Wi-Fi standards — 802.11a/b/g/n/ac — plus a choice of internal or external antennas, the VC80 can deliver desktop wired-line style performance on the most complex applications.

Repairable, right on the spot

Since the touchscreen — the most frequently damaged component — is field replaceable, trips to the service depot are eliminated, increasing device availability and your return on investment.

Pair Bluetooth devices in a split second

Need a separate handheld scanner? With a quick scan of the pairing bar code printed on the VC80 with Zebra's LS3478 or DS3578 handheld or RS507 ring-style cordless scanners, your workers are up and running.

Comprehensive Windows operating system (OS) support

The VC80 supports Embedded Standard 7 or Windows 7 Professional, and is Windows 10 ready, making it easy to extend virtually any PC-based app to your material handling vehicles.

VC80 Specifications Chart

Dimensions	10.4 in. L x 9.3 in. W x 3.5 in. D 265 mm L x 235 mm W x 90 mm D
Weight	8.6 lbs./3.9 kg
Keyboard Options	External QWERTY and AZERTY, optional L-mount
Power	Internal power supply 12-48V nominal, designed for forklift power
UPS and Backup Battery	Rechargeable UPS battery for operation during power loss; internal rechargeable battery for multiple months of real-time clock backup
Display	10.4 in. color XGA (1024 x 768) LCD; 24-bit color depth; choice of 400 or 1,000 NITs; LED backlight
Touchscreen:	Resistive touchscreen with passive stylus or finger operation Freezer version: integrated touchscreen heater evaporates external condensation when moving out of and into freezers
Keys	Six (6) programmable macro keys; keyboard key; volume; brightness; blue key for 2nd level functions; on/off key
Interface Ports	Standard sealed and secured connectors: 2 RS-232 serial ports; 1 standard USB port; 1 powered USB port; 13.5 mm audio jack; optional Ethernet (10/100/1000 Mbps) or isolated CAN port with SAE J1939 support
Indicators	Power LED; warning LED; blue key status LED
Scanner Support	Handheld scanners and imagers connected via USB, RS-232 or Bluetooth
Mounting	Quick release mount; standard RAM mounts; adapters for legacy vehicle computer mounts
PERFORMANCE C	HARACTERISTICS
CPU and RAM	Intel E3825 Dual Core, 1.33 GHz with 2 GB RAM or Intel E3845 Quad Core, 1.91 GHz with 4 GB RAM
Operating System	Windows Embedded Standard 7, 64 bit; Windows 7 Professional, 64 bit; Windows 10 ready
Mass Storage	mSATA SSD: 32 or 64 GB
Internal Expansion Slots	Two (2) PCle mini slots (one standard, one optional); one (1) M.2 slot
Additional Software	My-T-Soft configurable on-screen keyboard; Scanner Wedge with code manipulations; Scanner Management Service (SMS)
Optional Software	Wavelink Terminal Emulation (TE) 3270, 5250, VT100, VT220 (pre-loaded and pre-licensed on specific models); TekTerm; Mobile Device Management
Application Development	Standard Windows plus WMI additions
USER ENVIRONME	ENT
O	-22° to 122° F/-30° to 50° C
Operating Temp.	22 to 122 17 30 to 30 C

Humidity	5% to 95% non-condensing (standard version) 5% to 95% condensing (freezer version with internal heating)
Sealing	IP66
Thermal Shock	-22° to 122° F/-30° to 50° C
Shock/Vibration	IEC 60721-3-5M3; MIL-STD 810G; Method 514.6; MIL-STD 810G; Method 516.6
Salt Fog	48 hours of 5% solution at 35° C
Solar Radiation	MIL STD 810-G, Method 505.5, Procedure I
Integrated Sensors	Motion (accelerometer); temperature; ignition
ESD	±15kV air discharge, ±8kV direct discharge
WIRELESS DATA CO	OMMUNICATIONS
WLAN	IEEE 802.11a/b/g/n/ac 2x2 MIMO
WLAN Antennas	Internal or external
WPAN	Bluetooth V2.1 + EDR (Window 7/10) Bluetooth V4.0 Smart Ready (Windows 10)
GPS	Optional with DGPS support
VOICE AND AUDIO	•
Audio	High volume 87 dBA speaker
Push-to-Talk	External optional speaker/microphone
REGULATORY	
Electrical Safety	UL/cUL/IEC/EN 60950-1 Indoor use and UL/cUL/IEC/EN 60950-22 Outdoor use
EMI/RFI	North America: FCC Part 15, Class B Canada: ICES 003 Class B EU: EN55022, EN 301 489-1, EN 301 489-17
WLAN/Bluetooth	USA: FCC Part 15.247, 15.407 Canada: RSS-210 EU: EN 300 328, EN 301 893 AU/NZ: AS/NZS 4268
Environmental	RoHS/WEEE/REACH compliant
Flammability	IEC UL94-V0
ACCESSORIES	
microphone; keyboard for drop in replacemen	less scanners; antennas; push-to-talk speaker/ s; keyboard mounts; adaptation kits (power cables ts of legacy vehicle mount computer installations; AM mounts; scanner holder (for a complete list of .zebra.com/vc80)
WARRANTY	
is warranted against d	f Zebra's hardware warranty statement, the VC80 efects in workmanship and materials for a period o ate of shipment. For complete warranty statement,

The VC80 is ideal in...

Industries

- Warehousing
- Distribution
- Transportation & Logistics
- Manufacturing

Environments

- Freezers
- · Outdoor yards
- Airports
- Seaports
- Railway yards

Applications

- Receiving
- Picking
- Packing
- Shipping
- Replenishment
- Cross-dock
- · Work in Process (WIP)



NA and Corporate Headquarters +1 800 423 0442 inquiry4@zebra.com Asia-Pacific Headquarters +65 6858 0722 contact.apac@zebra.com

Zebra OneCare Select

EMEA Headquarters zebra.com/locations mseurope@zebra.com

Latin America Headquarters +1 847 955 2283 la.contactme@zebra.com







Zebra VC80 Forklift Terminal

Item number	Description
VC8010FSAA- 11CAAAXX	10" (1024 X 768), Freezer (-30 - +50 C, Condensing), Standard Display, Intel E3825 Dual Core, 1.33 Ghz, 1 Mb Cache, 2 Gb Ram, 32 Gb Ssd, Windows Embedded Standard 7, English, Tekterm, Basic Io, Int. Antennas
VC8010SOAA11CAB- AXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Outdoor Readable Display, Intel E3825 Dual Core, 1.33 Ghz, 1 Mb Cache, 2 Gb Ram, 32 Gb Ssd, Windows Embedded Standard 7, English, Tekterm, Basic Io, Connectors For Ext. Antennas
VC8010SOBB21CCB- CXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Outdoor Readable Display, Intel E3845 Quad Core, 1.91 Ghz, 2 Mb Cache, 4 Gb Ram, 64 Gb Ssd, Windows 7 Pro, English, Tekterm, Basic Io Plus Can-Bus, Connectors For Ext. Antennas, Gps
VC8010S- SAA00AAAAXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Standard Display, Intel E3825 Dual Core, 1.33 Ghz, 1 Mb Cache, 2 Gb Ram, 32 Gb Ssd, Basic Io, Int. Antennas
VC8010SSAA- 11CAAAXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Standard Display, Intel E3825 Dual Core, 1.33 Ghz, 1 Mb Cache, 2 Gb Ram, 32 Gb Ssd, Windows Embedded Standard 7, English, Tekterm, Basic Io, Int. Antennas
VC8010SSAA11CAB- AXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Standard Display, Intel E3825 Dual Core, 1.33 Ghz, 1 Mb Cache, 2 Gb Ram, 32 Gb Ssd, Windows Embedded Standard 7, English, Basic Io, Tekterm, Connectors For Ext. Antennas
VC8010SSAA11C- BAAXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Standard Display, Intel E3825 Dual Core, 1.33 Ghz, 1 Mb Cache, 2 Gb Ram, 32 Gb Ssd, Windows Embedded Standard 7, English, Tekterm, Basic Io Plus Ethernet, Int. Antennas
VC8010SSBB00AB- BAXX	10" (1024 x 768), Standard (-30 - $+50$ C, Non-Condensing Environments), Standard Display, Intel E3845 Quad Core, 1.91 GHz, 2 MB Cache, 4 GB RAM, 64 GB SSD, No Operating System, Basic IO plus Ethernet, connectors for external antennas
VC8010SSBB21CB- BAXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Standard Display, Intel E3845 Quad Core, 1.91 Ghz, 2 Mb Cache, 4 Gb Ram, 64 Gb Ssd, Windows 7 Pro, English, Tekterm, Basic Io Plus Ethernet, Connectors For Ext. Antennas
VC8010SSBB21C- CAAXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Standard Display, Intel E3845 Quad Core, 1.91 Ghz, 2 Mb Cache, 4 Gb Ram, 64 Gb Ssd, Windows 7 Professional, English, Tekterm, Basic Io Plus Can-Bus, Int. Antennas
VC8010SSBB21C- CBAXX	10" (1024 X 768), Standard (-30 - +50 C, Non-Condensing), Standard Display, Intel E3845 Quad Core, 1.91 Ghz, 2 Mb Cache, 4 Gb Ram, 64 Gb Ssd, Windows 7 Professional, English, Tekterm, Basic Io Plus Can-Bus, Connectors For Ext. Antennas

Accessories

Item number	Description
20667-002	Antenna, 802.11 b/g - dipole 2 dBi reverse polarity SMA connector (stubby)
AN000090A01	Antenna Active Gnss L1 Band Sma Plug 2.9M Rg316Ds Cable
AN2010	Antenna, dual band, 802.11 a/b/g/n, 2 dBi, RPSMA connector, magnetic mount, 2.9m
AN2020	Antenna, 2.4 GHz, 802.11 b/g, 5 dBi, RPSMA connector, magnetic mount, 2.9m
AN2030	Whip antenna (stubby), dual band, 802.11 a/b/g/n, 2.4GHz 2dBi, 5GHz 3.7 dBi, RPSMA connector
AR1000	Right Angle SMA reverse polarity plug-jack Adapter







Accessories

Item number	Description
9010376	iKey Keyboard, English, backlight, USB
9010377	iKey Keyboard, colour, English, USB
SLK-101-M-USB-3F	KEYBOARD:STANDARD
KT-SPRTCT-VC70-05R	Kit: Screen protector, VC70, set of 5
M1000	Speaker/Mic with push-to-talk function
SL0001	Stylus and Stylus Holder
KT-KYBDMNT-VC80-R	Function/Numeric Keypad Side Mount Bracket
KT-KYBDTRAY-VC80-R	Keyboard Mounting Tray. Includes Tilting Arms, Knobs And Screws. For Vc80 And Ikey Keyboards
KT-SCANMNT-VC80-R	Side Mounted Holder For Scanner
MT3501	VESA plate
MT3502	Round plate
MT3505	Clamp base (for 4" or 12" RAM arm), 2" max. width
MT3507	Clamp base (for 4" or 12" RAM arm), 3" max. width
MT3509	Rail base (for 4" or 12" RAM arm), 1-1/4" to 1-7/8"
MT3510	Rail base (for 4" or 12" RAM arm), 2" to 2 1/2"
MT4200	Quick release mount
MT4205	Mounting plate for MT4200 Quick Release Mount
MT4210	Adapter bracket kit for 82XX quick release mount
MT4301	RAM mount, 4" arm
MT4302	RAM mount, 12" arm
MT4510	RAM rectangular base with 2.25" rubber ball
CA1210	Power Extension Cable, DC, 6', waterproof
CA1220	Power Extension Cable DC, 6', waterproof - Screen Blanking
CA1230	Power extension cable for pre-regulator with ignition sense
CA1300	Screen blanking cable (DB9 to open wires)
CB-000433-01	Cable, Assembly, Vc80 Can Cable To Deutsch Connector
CB000416A01	DC Power Adapter to VC70 Extension Cable
CB000417A01	DC Power Adapter to VC50 Extension Cable
PS1370	Pre-Regulator, 19 - 90 VDC in, 15 VDC out, 90 W
PS1450	AC/DC Power Supply 18V 3.3A 110/220V
KT-VC80-SCRH1-01	FRONT WITH TOUCH SCREEN (HEATED)
KT-VC80-SCRN1-01	FRONT WITH TOUCH SCREEN (NON-HEATED)







Item number	Description
OSB-VC80XX-10	1 YEAR ON SITE SUPPORT. INCLUDES COMPREHENSIVE COVERAGE. CHECK DATASHEET FOR REGIONAL AVAILABILITY.
SCE-VC80XX-10	1 YEAR ZEBRA ONECARE SERVICE CENTER ESSENTIAL. INCLUDES COVERAGE FOR KEYBOARD. DOES NOT INCLUDE COMPREHENSIVE COVERAGE.
SCS-VC80XX-10	1 YEAR ZEBRA ONECARE SERVICE CENTER SELECT. INCLUDES COVERAGE FOR KEYBOARD. DOES NOT INCLUDE COMPREHENSIVE COVERAGE. (REQUIRES CUSTOMER-SUPPLIED SPARES POOL IN NA, NOT AVAILABLE FOR LA.)
SOB-VC80XX-30	3 YEAR SERVICE FROM THE START ON SITE BRONZE. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE. CHECK DATASHEET FOR REGIONAL AVAILABILITY.
SOB-VC80XX-50	5 YEAR SERVICE FROM THE START ON SITE BRONZE. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE. CHECK DATASHEET FOR REGIONAL AVAILABILITY.
SSE-VC80XX-10-R	1 YEAR ZEBRA ONECARE ESSENTIAL RENEWAL. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE.
SSE-VC80XX-20-R	2 YEAR ZEBRA ONECARE ESSENTIAL RENEWAL. INCLUDES COVERAGE FOR KEYBOARD. IN- CLUDES COMPREHENSIVE COVERAGE. CAN ONLY BE ORDERED ONCE AFTER INITIAL ZEBRA ONECARE CONTRACT EXPIRES
SSE-VC80XX-30	3 YEAR ZEBRA ONECARE ESSENTIAL. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE
SSE-VC80XX-50	5 YEAR ZEBRA ONECARE ESSENTIAL. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE
SSS-VC80XX-10-R	1 YEAR ZEBRA ONECARE SELECT RENEWAL. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE. (REQUIRES CUSTOMER-SUPPLIED SPARES POOL IN NA, NOT AVAILABLE FOR LA.)
SSS-VC80XX-20-R	2 YEAR ZEBRA ONECARE SELECT RENEWAL. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE. (REQUIRES CUSTOMER-SUPPLIED SPARES POOL IN NA, NOT AVAILABLE FOR LA.) CAN ONLY BE ORDERED ONCE AFTER INITIAL ZEBRA ONECARE CONTRACT EXPIRES
SSS-VC80XX-30	3 YEAR ZEBRA ONECARE SELECT. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE. (REQUIRES CUSTOMER-SUPPLIED SPARES POOL IN NA, NOT AVAILABLE FOR LA.)
SSS-VC80XX-50	5 YEAR ZEBRA ONECARE SELECT. INCLUDES COVERAGE FOR KEYBOARD. INCLUDES COMPREHENSIVE COVERAGE. (REQUIRES CUSTOMER-SUPPLIED SPARES POOL IN NA, NOT AVAILABLE FOR LA.)
OPT-COMM-10	1 Year Commissioning Option. Cannot be ordered alone.
OPT-COMM-20	2 Year Commissioning Option. Cannot be ordered alone.
OPT-COMM-30	3 Year Commissioning Option. Cannot be ordered alone.
OPT-COMM-50	5 Year Commissioning Option. Cannot be ordered alone.
OPT-DASHBOARD-10	1 Year Asset Visibility Dashboard Access. Cannot be ordered alone. Must be purchased together with a Zebra OneCare Essential agreement.
OPT-DASHBOARD-20	2 Year Asset Visibility Dashboard Access. Cannot be ordered alone. Must be purchased together with a Zebra OneCare Essential agreement.
OPT-DASHBOARD-30	3 Year Asset Visibility Dashboard Access. Cannot be ordered alone. Must be purchased together with a Zebra OneCare Essential agreement.







Item number	Description
OPT-DASHBOARD-50	5 Year Asset Visibility Dashboard Access. Cannot be ordered alone. Must be purchased together with a Zebra OneCare Essential agreement.
OPT-EXPSHIP-10	1 Year Express Shipping Option. Cannot be ordered alone. Available in NALA only.
OPT-EXPSHIP-20	2 Year Express Shipping Option. Cannot be ordered alone. Available in NALA only
OPT-EXPSHIP-30	3 Year Express Shipping Option. Cannot be ordered alone. Available in NALA only
OPT-EXPSHIP-50	5 Year Express Shipping Option. Cannot be ordered alone. Available in NALA only
OPT-VC80XXFSTRK-30	FASTRACK OPTION MUST BE PURCHASED UP FRONT WITH THE HARDWARE (OR WITHIN 30 DAYS THEREAFTER), TOGETHER WITH A 3-YR ZEBRA ONECARE SELECT AGREEMENT-AVAILABLE IN THE UK, BELGIUM AND NETHERLANDS ONLY
COM-SOTI-SV3	Commissioning of 1 SOTI MobiControl server and device config for up to 3 diff mobile device types (Zebra MC, Apple iOS or Google Android based devices). Hotel & Travel is extra and not discountable. See product note tab. USA & CANADA ONLY. Contact: rrquote@zebra.com for a quote
MDM-COM-000	Commissioning of 1 SOTI MobiControl server and device configuration for up to 3 different mobile device types (Zebra MC, Apple iOS or Google Android based devices). Costs for Hotel and Travel see product note tab. EMEA and APAC ONLY
MDM-COM-001	Commissioning of multiple SOTI MobiControl server and/or configuration not supported by Standard Commissioning service. Please contact your Zebra sales rep for details. Minimum order quantity is 10 licenses. • Contact: rrquote@zebra.com for a quote
MDM-COM-100	Commissioning of 1 SOTI MobiControl server and device configuration for up to 3 different mobile device types (Zebra MC, Apple iOS or Google Android based devices). Costs for Hotel and Travel see product note tab. EMEA and APAC ONLY
SW-SOTI-CLOUD	Subscription Pricing with SOTI dedicated cloud server - includes Standard Support. (SOTI PART# SOTI-MCL-DEV)
SW-SOTI-MCADDON	Additional Perpetual License for existing reg code. (SOTI PART# SOTI-MCP-DEV)
SW-SOTI-MCL-DEF	If Cloud SaaS device instance is less than seventy-five (75) licenses, instance fee applies until such time the instance surpasses 75 licenses. (SOTI PART# SOTI-MCL-DEF)
SW-SOTI-MCNOMAINT	SOTI MobiControl Perpetual Client License. Must purchase minimum 1 year maintenance. Pre-Existing SOTI Deployments Must co-terminate maintenance contracts with equivalent months of maintenance. MIN ORDER QTY is 10 Licenses for new deployments and 5 Licenses for add-on orders. (SOTI PART# SOTI-MCP-DEV)
SW-SOTI-SAAS	Subscription Pricing for customers who install on their own hardware - includes Standard Support. (SOTI PART# SOTI-MCS-DEV)
SW-SOTISERVER	MobiControl Server License - Initial purchase of SOTI Mobicontrol requires the purchase of 1 or More Server Licenses. Clients can be added to existing instances of SOTI Mobicontrol. (SOTI PART# SOTI-SERVER)
SWS-SOTIMC-10	1 Year Software Support for SOTI. Includes technical support and software updates. Priced per license. Minimum order quantity is 10 licenses. (SOTI PART# SOTI-MCP-MNT (old part # SOTI-MC-PREM-MAINT-1MO)
SWS-SOTIMC-1M	Adds 1 Month of Software Support for SOTI to existing contracts . Includes technical support and software updates. Priced per license. Must be ordered with a Soti license. Minimum order quantity IS 10 licenses.
SWS-SOTIMC-20	2 Year Software Support for SOTI. Includes technical support and software updates. Priced per license. Minimum order quantity is 10 licenses.







Item number	Description
SWS-SOTIMC-30	3 Year Software Support for SOTI. Includes technical support and software updates. Priced per license. Minimum order quantity is 10 licenses.
ZSOTI-CON-MIG-HRL	SOTI MIGRATION SERVICES INCLUDING PLANNING, INSTALLATION & CONFIGURATION OF SERVER AND DEVICES - PRICE PER HOUR
ZSOTI-IMP-HRL	SOTI JUMPSTART IMPLEMENTATION SERVICE PER HOUR CHARGE (GREAT ER T HAN 1,000 DEVICES, QUOTE ON NUMBER OF HOURS TO BE FIR MED POST DISCOVERY CALL WITH THE CUSTOMER)
ZSOTI-MCX-ADV-1MO	SOTI Advantage Support is an add-on to standard support. 24x7 level 1 support Price is per device, per month
ZSOTI-MCX-ENT-1MO	SOTI MOBICONTROL ENTERPRISE SUPPORT add-on to standard maintenance support Price per device, per month. minimum quarterly charge applied if under 300 devices ZSOTI-MCX-ENT-MIN
ZSOTI-MCX-ENT-MIN	SOTI MOBICONTROL ENTERPRISE SUPPORT (IF LESS THAN 300 DEVICES, ADDITIONAL QUARTERLY CHARGE) ASSESSED EACH QUARTER UNTIL AT LEAST 300 DEVICE MANAGED
ZSOTI-PSS-TRN-3EX	SOTI ACADEMY CERTIFICATION EXAM FEE (BUNDLE OF 3 EXAMS)
ZSOTI-PSS-TRN-EXM	SOTI ACADEMY CERTIFICATION PER EXAM FEE (PER PERSON)
ZSOTI-TRN-ACT	SOTI ACADEMY CERTIFIED MOBICONTROL ASSOCIATE TRAINING COURSE (LEVEL 1)
ZSOTI-TRN-ALL	SOTI ACADEMY ON DEMAND TRAINING, ALL LEVELS
ZSOTI-TRN-BOT-ATT	SOTI MOBICONTROL ADDITIONAL ATTENDEE FOR BOOTCAMP 3-DAY TRAINING (TRAVEL & EXPENSES ADDITIONAL). PRICE PER PERSON.
ZSOTI-TRN-BOT-ONS	SOTI MOBICONTROL BOOTCAMP ONSITE 3-DAY TRAINING (TRAVEL & EXPENSES ADDITIONAL). PRICE PER SESSION, MAX ATTENDEES PER SESSION IS 5.
ZSOTI-TRN-EXP	SOTI ACADEMY CERTIFIED MOBICONTROL EXPERT TRAINING COURSE (LEVEL 3)
ZSOTI-TRN-PRF	SOTI ACADEMY CERTIFIED MOBICONTROL PROFESSIONAL TRAINING COURSE (LEVEL 2)
SWE-82990-01	Wavelink Traditional Green Screen Terminal Emulation Client VT/HP (for Window & Android devices)
SWE-82990-02	Wavelink Traditional Green Screen Terminal Emulation Client 5250/3270 (for Window & Android devices)
SWE-82990-03	Wavelink Traditional Green Screen Terminal Emulation Client 4 in 1 (For Window & Android devices)
SWS-WL-TN-2IN1-10	1 Year Software Support for Wavelink Telnet Client 2 in 1
SWS-WL-TN-2IN1-30	3 Year Software Support for Wavelink Telnet Client 2 in 1
SWS-WL-TN-4IN1-10	1 Year Software Support for Wavelink Telnet Client 4 in 1
SWS-WL-TN-4IN1-30	3 Year Software Support for Wavelink Telnet Client 4 in 1
C-OTT-WIN32	License Open TekTerm
C-OTT-WINCE	License Open TekTerm
C-OTT-WM	License Open TekTerm
SW9510L	License Commserver Lite (maintenance is manditory for first year)
SW9510S	License Commserver Standard (maintenance is manditory for first year)







Item number	Description
SW9510TSFO	License WINTSFO (maintenance is manditory for first year)
SWS-SW95XX-10	Commserver Maintenance 1 Year
SWS-SW95XX-20	Commserver Maintenance 2 Year
SWS-SW95XX-30	Commserver Maintenance 3 Year
SWS-TEKTRMCLNT-10	1 year maintenance for TekTerm Client (TekTerm Server maintenance is to be purchased seperately)
SWS-TEKTRMCLNT-20	2 years maintenance for TekTerm Client(TekTerm Server maintenance is to be purchased seperately)
SWS-TEKTRMCLNT-30	3 years maintenance for TekTerm Client(TekTerm Server maintenance is to be purchased seperately)
SW-WL-SPEAKEASY	Wavelink Speakeasy Voice Client (One Client per Device). Note, one or three year software support to be ordered in addtion at time of purchase.
SWS-SPKEASY-10	1 Year Software Support for Speakeasy. Includes techical support and software updates. Priced per license
SWS-SPKEASY-30	3 Year Software Support for Speakeasy. Includes techical support and software updates. Priced per license

MORE ZEBRA FORKLIFT TERMINALS

