

# VEHICLE CRADLE FOR HONEYWELL DOLPHIN 99EX

---

## TISLPUS Active Vehicle Cradle for Dolphin 99ex

The vehicle cradle for Dolphin 99ex is a TIS development. It impresses with its functional and compact, but still robust design. The easy insertion of the Dolphin 99ex with secure locking mechanism allows operation with only one hand.

---

Installation is also simple: screwing from the front allows for easy installation on the dashboard.

The cradle has a wide input voltage range of 9-30V. With an operating temperature of -20 °C to +70 °C the cradle goes through temperature fluctuations without any problems and does not limit the application range of the Dolphin 99ex.

---

### AT A GLANCE

- Functional and stylish, yet durable design
- Rock & Lock™ mechanism allows
- Easy insertion of the device with secure locking mechanism (allows one-hand operation!)
- Internal protected plugs for secure connections
- Cable outlets in different directions (side, bottom, rear) in the cap
- Screwing from the front allows easy installation on the dashboard
- Optional: Integrated Smart Card Reader
- Optional interfaces for peripheral devices
- 100% Made in Germany

### SPECIAL CHARACTERISTICS

Screwing from the front ensures easy mounting



Protected plugs and simple cable protection (example: supply and USB cables)



Cradle only, device and Smart Card Reader not included

---

### NOTE

Our vehicle cradles are delivered with a "charging only" function by default. On request, we integrate options, such as USB or Smart Card Reader for reading of driver cards (digital speedometer) and other smart cards.

# VEHICLE CRADLE FOR HONEYWELL DOLPHIN 99EX

## TECHNICAL SPECIFICATIONS

---

### SIZE AND WEIGHT

- 150 x 89 x 86 mm
- 340g (without device)

---

### VOLTAGE RANGE

- 9-30V

---

### INTERFACE

- USB Client interface (optional)

---

### CONFORMITY

- e1 Approval
- Interference resistance after EN 61000-6-2
- Transient emissions after EN 61000-6-3

---

### DISPLAY LED

- Display LED for power supply

---

### APPLICATION AREA

- Operating temperature: -20°C to +70
- Storage temperature: -45°C to +80°C

---

### ITEM NUMBERS

24-99-09-TVCM-01	charging only
24-99-09-TVCM-02	with USB Host connection
24-99-09-TVCM-03	with Smart Card Reader
24-99-09-TVCM-04	with USB and Smart Card Reader
24-99-09-TVCM-05	with USB Client

---

### POWER SUPPLY

- Power outlet +5V / 200mA

---

### SMART CARD READER (optional)

- optional
- Card voltage: 5V, 3V, 1,8V max. 60mA
- Protocols: T=0, T=1
- Data rate up to 420kBits/s

---

### ACCESSORY

For the Dolphin 99ex besides our own accessories we hold a wide range of accessories from well-known manufacturers ready, such as quivers, batteries, styluses, display protecting foils, charging- and docking stations, etc.

We will be happy to send you more information on demand. Just contact us!

---