

VEHICLE CRADLE FOR HONEYWELL 70e/75e

The TISPLUS vehicle cradle for Honeywell 70e (IP67) and 75e impresses by its functional and compact, but still robust design.

The easy insertion of the device with secure locking mechanism allows operating it with only one hand.

ITEM NUMBERS

24-70-09-TPC-01 for Dolphin 70e (IP67) / 75e Charge Only (cradle only, device and RAM mount not included)

24-70-09-TPC-02 for Dolphin 70e (IP67 / 75e with Audio Output for Passive 8 Ohm Speaker (cradle only, device and RAM mount not included)

Installation is simple: screw holes in the front allow easy fixed mount installation on the dashboard or a mobile installation with RAM mount and suction cup (RAM mount not included). The cradle has a wide input range of 9-30V and the Audio version makes the devices USB interface available via micro-USB connector on the cradle.

With an operating temperature of -20 °C to +70 °C the cradle withstands temperature fluctuations without any problems and does not limit the application range of the Honeywell Dolphin 70e and 75e.

AT A GLANCE

- Functional and stylish, yet durable design
- Easy insertion of the device with secure locking mechanism and one-hand operation
- Protected pogo pins for secure connections
- Audio version allows to connect a passive speaker with 8 Ohm (not included) and features a mini-USB connector, which allows to access the USB port of the device
- Screwing from the front allows easy installation to the dashboard
- RAM mount compatible, many options for installation available
- 100% Made in Germany

TECHNICAL SPECIFICATIONS

DIMENSIONS

136 x 84 x 59 mm

OPERATING TEMPERATURE

-20°C to +70°C

STORAGE TEMPERATURE

-45°C to +80°C

WEIGHT

244g (without device)

VOLTAGE RANGE

9-30V

CONFORMITY

- e1 Approval
 - European Conformity Marking
-

