

## VEHICLE CRADLE FOR ZEBRA MC55/65/67

---

### TISPLUS Active Vehicle Cradle for Zebra MC55/65/67

The TISPLUS vehicle cradle for Zebra MC55/65/67 is a TIS development. It impresses by its functional and compact, but still robust design. The easy insertion of the device with secure locking mechanism allows for operation with only one hand.

---

Installation is also simple: screwing from the front allows for easy installation on the dashboard. The cradle has a wide input voltage range of 9-30V.

With an operating temperature of -20 °C to +70 °C the cradle goes through temperature fluctuations without any problems and does not limit the application range of the Zebra MC55/65/67.

#### AT A GLANCE

- Functional and stylish, yet durable design
- "Rock & Lock" mechanism allows
- Easy insertion of the device with secure locking mechanism (one-hand operation!)
- Internal protected plugs for secure connections
- Cable outlets in different directions (side, bottom, rear) in the cap
- Screwing from the front allows easy installation on the dashboard
- Optional: Integrated Smart Card Reader
- Optional interfaces for peripheral devices
- 100% Made in Germany

#### SPECIAL CHARACTERISTICS

Screwing from the front ensures easy mounting



Protected plugs and simple cable protection (example: supply and USB cables)



Cradle only, device and Smart Card Reader not included

---

#### NOTE

Our vehicle cradles are delivered with a "charging only" function by default. On request, we integrate options, such as USB or Smart Card Reader for reading of driver cards (digital speedometer) and other smart cards.

# VEHICLE CRADLE FOR HONEYWELL DOLPHIN 7800

## TECHNICAL SPECIFICATIONS

### SIZE AND WEIGHT

- 150 x 89 x 86 mm
- 340g (without device)

### VOLTAGE RANGE

- 9-30V

### INTERFACES

- USB Host interface (e.g. for printers) optional
- Optionally one or two serial interfaces

### CONFORMITY

- e1 Approval
- Interference resistance after EN 61000-6-2
- Transient emissions after EN 61000-6-3

### DISPLAY LED

- Display LED for power supply

### APPLICATION AREA

- Operating temperature: -20°C to +70
- Storage temperature: -45°C to +80°C

### ITEM NUMBERS

23-55-09-TVCM-01	charging only
23-55-09-TVCM-02	with USB Interface
23-55-09-TVCM-03	with Smart Card Reader
23-55-09-TVCM-04	with USB Interface and Smart Card Reader
23-55-09-TVCM-05	with one Serial Port
23-55-09-TVCM-06	with two Serial Ports

### POWER SUPPLY

- Power outlet +5V / 200mA

### SMART CARD READER

- optional
- Card voltage: 5V, 3V, 1,8V max. 60mA
- Protocols: T=0, T=1
- Data rate up to 420kBits/s

### ACCESSORY

For MC55/65/67 besides our TISPLUS accessories we hold a wide range of accessories from well-known manufacturers ready.

We will be happy to send you more information on demand. Just contact us.