

VEHICLE CRADLE FOR HONEYWELL CN51

The TISPLUS vehicle cradle for Honeywell CN51 impresses by its functional and compact, but still robust design.

The easy insertion of the device with secure locking mechanism allows operating it with only one hand.

ITEM NUMBER

24-51-09-TPC-01 (cradle only, device and RAM mount not included)

Installation is simple: screw holes in the front allow easy fixed mount installation on the dashboard or a mobile installation with RAM mount and suction cup (RAM mount not included).

The cradle has a wide input voltage range of 9-30V and makes the CN51 USB interface available via micro-USB connector on the cradle.

With an operating temperature of -20 °C to +70 °C the cradle withstands temperature fluctuations without any problems and does not limit the application range of the Honeywell CN51.

AT A GLANCE

- Functional and stylish, yet durable design
- Easy insertion of the device with secure locking mechanism and one-hand operation
- Protected pogo pins for secure connections
- The CN51 USB On-The-Go interface is available on the cradle as micro-USB connector
- Screwing from the front allows easy installation to the dashboard
- RAM mount compatible, many options for installation available
- 100% Made in Germany

TECHNICAL SPECIFICATIONS

DIMENSIONS

136 x 84 x 59 mm

OPERATING TEMPERATURE

-20°C to +70°C

STORAGE TEMPERATURE

-45°C to +80°C

WEIGHT

244g (without device)

VOLTAGE RANGE

9-30V

CONFORMITY

- e1 Approval
 - European Conformity Marking
-

